



Terrific Direct-to-Metal Adhesion and VOC Flexibility

7000 Epoxy Primer is a two-component high-solid epoxy primer designed for the vehicle refinish market. It is easy to apply; providing excellent holdout and a smooth final appearance. 7000 Epoxy Primer is a versatile, user-friendly product that is good over multiple substrates; making it ideal for a wide range of vehicle repairs. It can be applied over polyester filler and offers terrific flow and holdout, durability and DTM adhesion.

Product Features

- 3:1 Mix ratio
- Direct-to-metal
- · Terrific sprayability
- VOC flexibility
- Consistent performance

Your Benefit

- Easy to use
- Eliminates pre-treats, shortens process
- Great flow and leveling, smooth surface
- National Rule and 2.1 compliant
- Air dry or bake



7000 Epoxy Primer





7000 Epoxy Primer is a two-component high-solid epoxy primer designed for the vehicle refinish market. It is easy to apply; providing excellent holdout and a smooth final appearance.

Product and Additives

Product - Wanda 7000 Epoxy Primer

Hardener - Wanda 7000 Epoxy Hardener

Additive - None



3 parts by volume of Wanda 7000 Epoxy Primer 1 part by volume Wanda 7000 Epoxy Hardener

Application Process

Apply one to two single flowing coats

Flash Time

Allow for 10 minutes flash time between coats

Drying Times

Wanda 7000 Epoxy Hardener

70°F (20°C) 140°F (60°C)

Before topcoat 30-45 minutes

1-1.5 hours Dry to sand 24 hours

See the Wanda 7000 Epoxy Primer complete Technical Data Sheet for more detailed product and application information.











